

## PS SERIES 400 Hz - 60 Hz FREQUENCY CONVERTER



**MODEL NUMBER: PS-61-33D**

### INPUT:

Voltage Range	115/200 ± 20 VRMS
Configuration	3-Phase, delta or wye
Frequency Range	360 to 440 Hz
Protection	Circuit breaker, over/undervoltage, loss of phase, overcurrent, and phase rotation protection

### OUTPUT:

Power	8 kVA
Overload	9 kVA for 5 minutes at 10% duty cycle
Configuration	Single-Phase
Voltage	115 ± 3 VRMS under all conditions of line, load and temperature (120 VRMS optional)
Frequency Regulation	60 Hz ± 0.6 Hz under all conditions of line, load and temperature
Harmonic Distortion	5% maximum
Power Factor Range	0.75 lagging to 1.0
Efficiency	80% minimum
Protection	Overload and short circuit

ISO 9001



Registered to ISO 9001:2000

### APPLICATION:

Since 1960, Unitron has focused on the design and development of reliable solid-state power systems. The PS-61-33D is part of a family of frequency converters, which has seen extensive military and commercial use. The unit provides a precision source of 60 Hz power for the airborne operation of equipment normally used on the ground, or for ground systems where the prime input power is 400 Hz. It operates under a wide range of environmental conditions, and offers complete protection against misapplication of input power and output loading conditions.

### FEATURES:

Small Size and Light Weight • Full Protection of Both Input and Output • Wide Input Voltage and Frequency Variation • High Efficiency • Low Audio and Radio Noise Levels • High Reliability • Qualification Tested • Precision Output Voltage • All Silicon Solid State

### MECHANICAL:

Size:	12.2" height, 20.0" width, 23.5" depth
Weight:	230 lbs. maximum
Mounting:	Hard mount
Connectors:	Input: MS3102R24-22P Output: MS3102R28-5S
Cooling:	Self-contained fan (slow speed for low ambient noise)

### ENVIRONMENTAL:

Temperature	-55°C to +71°C operating; -65°C to +85°C storage
Altitude	15,000 ft. operating, 50,000 ft. storage
Shock	MIL-STD-202, Method 205
Vibration	MIL-STD-202, Method 201
Humidity	95% RH at 30°C
RFI	Radiated and conducted per MIL-I-6181D

REV. A

