

## UFC SERIES Low ProFile™ 400Hz GROUND POWER UNIT 60kVA to 90kVA



HORIZONTAL CONFIGURATION  
(Shown with standard 4 inch feet and touch screen panel)

### STANDARD FEATURES:

- IP55
- Certified to UL 1012
- 3 Phase, 380-480 VAC input
- Indoor/Outdoor (Hangar/Ramp) Use
- ≤ 5% Input Current Distortion at max load
- Automatic Input Line Monitoring
- Advanced Integrated Display (AID™) Console
- 8000 Event Log / Diagnostics
- TCP/IP/Ethernet interface (Modbus)
- Internal Communication Ports - USB, RS485 (Modbus), & RS232
- External Communication Port – USB
- 15% Automatic Line Drop Compensation
- Emergency Power “OFF” Switch
- I/O Voltage, Current, & Frequency Monitoring
- Elapsed Time Meter
- Sleep Mode
- Front Panel Voltage Adjust
- Front Panel Summary Fault Indicators
- 4 Inch Leg Kit
- Input High Voltage Transient Protection
- Multi Language Display - Arabic, Asian, English, French, German, Italian, Portuguese, Russian and Spanish, Others - Specify

### MECHANICAL SPECIFICATIONS:

Size:	See Figure 1
Weight:	60.0kVA = 773lbs. (351kg.) 75.0kVA = 850lbs. (386kg.) 90.0kVA = 937lbs. (425kg.)
Enclosure:	NEMA 250 - Type 3SX
Cooling:	Forced Convection

This product was manufactured in a plant whose quality management system is registered to ISO 9001:2015.



### APPLICATION:

Since its beginning in 1960, Unitron has specialized in the design and development of reliable solid-state power systems. Through an innovative design, advanced self-diagnostic systems (BITE) and modular construction, Unitron products assure maximum power availability and minimal repair time.

The Low ProFile Series includes 115/200VAC, 400Hz, 28VDC, and 270VDC converters designed to provide aircraft ground power in "low profile" applications such as under passenger boarding bridges, in maintenance hangars, or on flight lines. This versatile design is particularly well suited for field installations where low clearances for aircraft are required.

Output power ratings for the **400Hz Horizontal Low ProFile** Ground Power Unit (GPU) range from 20kVA to 180kVA. Larger power ratings are available in towable, fixed and bridge-mounted configurations. When ramp or floor space is a premium, the **Low ProFile** GPU can be installed as an overhead mounted unit.

In addition to fixed GPUs, Unitron offers mobile and towable configurations.

### OPTIONS:

- Alternate Input Voltage Range 3-phase, 208-240 or 600VAC Input
- Various Convenience Outlets (Specify Voltage and Frequency)
- 50 or 100 Foot Input Power Cable (Pigtail, Specify Required Length)
- AC Output Power Cable with Plug (Specify Required Lengths - Available in 30 or 60 foot standard lengths)
- External Communication Port - Ethernet
- Input & Output Cable Racks
- Output Universal Aircraft Safety Interlock Circuit Disconnect (Single or Dual)
- Output Safety Disconnect
- No Break Power Transfer Compatible
- Bench Top Voltage Adjust
- 28VDC or 270VDC Output
- Second 28VDC output
- 300% overload for 6 seconds or 425% overload for 1 second\* (Specify)
- RJ45 (Ethernet) Port - Internal or External (Specify)
- Indoor Touch Screen Panel
- Custom Paint & Decals (Standard Color - White)
- Ground Fault Monitor
- CSA Certified
- CE Mark Certified
- Alternate Mounting Configurations Available
- Stand - 4, 12 or 18 Inch\*\*
- Leg Kit - 12 or 18 Inch\*\*
- Forklift Tubes - 4 Inch
- Neutral Interrupt Protection
- Universal Safety Interlock

\* IAW MIL-STD-704F & ISO 6858: 2017

\*\* IAW NFPA 70, Article 513.10 (c) (1) - 18 Inch Rule (18" Leg Kit & Stand only)

### SPECIFICATIONS / STANDARDS (Meets or Exceeds):

NFPA 70 (NEC 500)	SAE ARP 5015
EN 60079-10	MIL-STD-1472
DFS-400	MIL-STD-704F
ISO 461-1/2	UFGS 26 35 43
ISO 1540	EN 61000-6-2 and -4**
ISO 6858	2006/95/EC**

\*\*\*Defined Basis of CE Mark Certification

**GENERAL SPECIFICATIONS**

**INPUT:**

Input Current Distortion	≤ 5%, typically 3%
Voltage	380 to 480 volts, +10%, -15%, 3Ø, 3 or 4 wire plus ground (Alternate Voltages Available)
Voltage Adjust	± 15%
Frequency	50 - 60 Hz ± 10%
Phase Rotation	Any
Protection	Over/undervoltage, loss of phase, overcurrent, short circuit. Voltage transient protection IAW IEEE C62.41.1, Location Cat. B/C
Inrush Current	No greater than 100% of full load current

**ENVIRONMENTAL:**

Acoustical Noise	< 65 dBA maximum at 5 feet (1.5m)
Temperature Range	-40°C to +55°C
Relative Humidity	10 - 95%, Non-Condensing
Ingress of Water	Type 3SX, IP55

**ENERGY FACTORS:**

Efficiency	94% typical at full load, 92% typical at half load; varies depending on configuration
Energy Efficiency Ratio	20.0 typical

**OUTPUT:**

Power Rating	60, 75, or 90 kVA (Specify)
Power Factor Range	0.5 lagging to 0.8 leading
Overload	100% continuous 110% for 60 min 125% for 10 min 150% for 2 min 200% for 20 sec
Voltage*	115/200 volts, 3Ø, 4 wire, grounded neutral
Voltage Adjust*	± 15%
Crest Factor	1.414 ± 3%
Voltage Regulation	± 1.0% under all conditions of line, balanced loads and temperature
Voltage Transients	IAW MIL-STD-704F
Frequency Regulation	400 Hz ± 0.01% under all conditions of line, load and temperature
Frequency Transients	None
Phase Angle Regulation	± 1° for balanced loads; ± 2° for unbalanced loads
Harmonic Distortion	2.0% maximum
Protection	Overload, short circuit, over/undervoltage and safety disconnect
Automatic Line Drop Compensation (ALDC)	15%

\*Also available 120/208 VAC, adjustable ±10%

FIGURE 1

