



MOBILE CONFIGURATION
(Shown in Ramp Only Configuration)

FoxAir Series Mobile HVAC 50Hz - 21,000 BTU

The FoxCart's FoxAir Series is a portable HVAC unit capable of delivering 21,000 BTU of refrigerated air for pre-cooling or maintenance operations, cooling 1,200 - 1,400 square feet, dependent upon ambient conditions. With an additional 11,000 BTU 'Heater' option, the FoxAir can create that comfortable climate year round.

STANDARD FEATURES:

- Integral 20A Breaker / Switch
- Only 20A Service Required
- Sealed Refrigerant System for Unmatched Reliability and Performance
- 547 CFM Air Movement System
- Infrared Remote Control with Display
- Washable Anti-Microbial Air Filter
- Quick-Connect Collar for Quick and Easy Connection of Air Delivery Hose
- Maintenance Free Tires and Locking Swivel Casters

INPUT:

Voltage Range	220 - 240 VRMS, 1Ø, 2 Wire, Plus Safety Ground
Frequency	50 Hz ± 10%
Compressor Rated Load	9.5 Amps
Safety Disconnect	Circuit Breaker ON / OFF

ENVIRONMENTAL:

Refrigerant Type / Qty	R410A - 47.3 oz
Moisture Protection	IP24
Air Filter	Washable
Sound Level	62 dBa

INDICATORS:

Min Ambient Temp	Cooling for ≈ 1,200 - 1,400 Sq. Ft. Area - 64°F
Max Ambient Temp	Heating - 110°F (Requires Heat Option)

OPTIONS:

- 11,000 BTU Heater
- Air Delivery Hose (Steel Reinforced 10" Diameter)
- Drain Hose Kit - 50' or 100' Feet (Specify)
- 50' or 100' Foot Input Power Cable (Pigtail - Specify)

MECHANICAL SPECIFICATIONS:

Size:	See Figure 1
Weight:	261lbs (119kg)

(Weight Varies with Options)

OPERATING CONDITIONS:

Adjustable Fan Speeds	Auto, Low, Medium, High
Modes	Auto, Cool, Dry, Fan Only

CONTROLS:

Timer	24 Hour
Temperature	via Remote

CAPACITY RATINGS (OUTPUT):

Cooling BTU / Tons	21,000 / 1.75
Heating (Optional)	11,000 BTU
Airflow	547 CFM
Moisture Removal	5.2 Pints per Hour
Energy Efficiency Ratings	
SEER	4.8
EER	3.0

GENERAL SPECIFICATIONS:

Specifications subject to change without notice

Rev C

