

UFC SERIES Low ProFile™ 400Hz AND 28VDC GROUND POWER UNIT (20kVA to 45kVA)



HORIZONTAL CONFIGURATION
(Shown with standard 4 inch stand and touch screen panel)

STANDARD FEATURES:

- IP55
- Certified to UL 1012
- Indoor/Outdoor (Hangar/Ramp) Use
- Automatic Input Line Monitoring
- Advanced Integrated Display (AID™) Console
- 8000 Event Log / Diagnostics
- TCP/IP/Ethernet interface (Modbus)
- Internal Communication Ports - USB, RJ45 (ETHERNET), RS485 (Modbus), & RS232
- External Communication Port – USB
- Emergency Power “OFF” Switch
- 18-Inch Hazard Area Clearance
- I/O Voltage, Current, & Frequency Monitoring
- Elapsed Time Meter
- Sleep Mode
- Front Panel Voltage Adjust
- Front Panel Summary Fault Indicators
- Output Current Limit Adjust from 150A to full rated current
- Input Frequency Monitoring
- Input & Output Cable Racks
- Input High Voltage Transient Protection
- Multi Language Display - Arabic, Asian, English, French, German, Italian, Portuguese, Russian and Spanish, Others - Specify

This product was manufactured in a plant whose quality management system is registered to ISO 9001:2015.



APPLICATION:

Since its beginning in 1960, Unitron has specialized in the design and development of reliable solid-state power systems. Through an innovative design, advanced self-diagnostic systems (BITE) and modular construction, Unitron products assure maximum power availability and minimal repair time.

The Low ProFile Series includes 115/200VAC, 400Hz, 28VDC, and 270VDC converters designed to provide aircraft ground power in "low profile" applications such as under passenger boarding bridges, in maintenance hangars, or on flight lines. The **dual output AC/DC GPU** provides simultaneous AC and either 425 or 600 amps continuous DC power from a single unit. Kilowatt power for the complete unit is limited to the nominal rating of the 400Hz output of the unit. Because a single unit can do the work of two, Unitron's AC/DC GPU reduces operating and maintenance costs, and save valuable space in the hangar or on the ramp.

In addition to fixed GPUs, Unitron offers 400Hz, 28VDC and combination AC/DC units in towable, mobile and bridge-mounted configurations.

OPTIONS:

- Alternate input voltage range 3 Phase, 208-240 or 600VAC input
- Various Convenience Outlets (Specify Voltage and Frequency)
- 50 or 100 Foot Input Power Cable (Pigtail, Specify Required Length)
- AC and/or DC Output Power Cable with Plug (Specify Required Length)
- Output Universal Aircraft Safety Interlock Circuit Disconnect (Single or Dual)
- External Communication Port - Ethernet
- ≤5% Input Current Distortion at Max Load
- 15% Automatic Line Drop Compensation
- Output Safety Disconnect
- Bench Top Voltage Adjust
- No Break Power Transfer Compatible
- 270VDC Output
- Second 28VDC output
- Custom Paint & Decals (Standard Color - White)
- CSA Certified
- CE Mark Certified
- Input Auto Ranging
- Ground Fault Monitor
- Lockable Front Door
- Pneumatic Ramp Tires
- Alternate Mounting Configurations Available
- Neutral Interrupt Protection
- Universal Safety Interlock

MECHANICAL SPECIFICATIONS:

Size:	See Figure 1
Weight:	20.0kVA = 701 lbs (318 kg)
	30.0kVA = 758 lbs (344 kg)
	45.0kVA = 845 lbs (383 kg)
Enclosure:	NEMA 250 - Type 3SX
Cooling:	Forced Convection

SPECIFICATIONS / STANDARDS (Meets or Exceeds):

NFPA 70 (NEC 500)	ISO 461-1/2
EN 60079-10	ISO 1540
UFGS 26 35 43	ISO 6858
DFS-400	MIL-STD-1472
SAE ARP 5015	MIL-STD-704F

**Defined Basis of CE Mark Certification

GENERAL SPECIFICATIONS

AC INPUT:

Voltage	380 - 480V, $\pm 10\%$, 3 \emptyset , 3 or 4 wire plus ground (Alternative Voltages Available)
Frequency	50 - 60 Hz $\pm 10\%$
Phase Rotation	Any
Protection	Over/undervoltage, loss of phase, overcurrent, short circuit. Voltage transient protection IAW IEEE C62.41.1, Location Cat. B/C
Inrush Current	No greater than 100% of full load current

AC OUTPUT:

Power Rating	20, 30, or 45 kVA (Specify)
Power Factor Range	0.5 lagging to 0.8 leading
Overload:	
100% continuous;	110% for 60 min;
125% for 10 min;	150% for 2 min;
200% for 20 sec (45kVA);	300% for 20 sec (30kVA);
450% for 20 sec (20kVA)	
Crest Factor	1.414 $\pm 3\%$
Voltage*	115/200 volts, 3 \emptyset , 4 wire, grounded neutral
Voltage Adjust*	$\pm 15\%$
Voltage Regulation	$\pm 1.0\%$ under all conditions of line, balanced loads and temperature
Voltage Transients	IAW MIL-STD-704F
Frequency Regulation	400 Hz $\pm 0.01\%$ under all conditions of line, load and temperature
Frequency Transients	None
Phase Angle Regulation	$\pm 1^\circ$ for balanced loads; $\pm 2^\circ$ for unbalanced loads
Harmonic Distortion	2.0% maximum
Protection	Overload, short circuit, over/under voltage and safety disconnect
Automatic Line Drop Compensation (ALDC)	15%

DC OUTPUT:

Model 420

Full Load Rating	425 amps continuous
Overload	600 amps for 1 hour
(10% duty cycle)	1000 amps for 1 minute

Model 620

Full Load Rating	600 amps continuous
Overload	1000 amps for 1 minute
(10% duty cycle)	

Model 420/620

Engine Start Capacity	Adjustable up to 1600 amps for 35 seconds or 2000 amps for 30 seconds
-----------------------	---

Voltage	28 VDC, 2 wire, grounded negative
---------	-----------------------------------

Voltage Regulation

<ul style="list-style-type: none"> 100% continuous rated load and $\pm 10\%$ input voltage No load to rated load with nominal input voltage Overload with nominal input voltage 	<ul style="list-style-type: none"> $\pm 0.5\%$ $\pm 0.5\%$ See start mode curves
---	---

Voltage Adjust	28 VDC $\pm 10\%$
----------------	-------------------

Current Limit Adjust	150A to full rated current
----------------------	----------------------------

Protection	Overload, short circuit, over voltage and safety disconnect
------------	---

Automatic Line Drop Compensation (ALDC)	10%
---	-----

ENVIRONMENTAL:

Acoustical Noise	< 65 dBA maximum at 5 feet (1.5m)
------------------	-----------------------------------

Temperature Range	-40°C to +55°C
-------------------	----------------

Relative Humidity	10 - 95%, Non-Condensing
-------------------	--------------------------

Ingress of Water	Type 3SX, IP55
------------------	----------------

ENERGY FACTORS:

Efficiency	93% typical at full load, 91% typical at half load; varies depending on configuration
------------	---

Energy Efficiency Ratio	20.0 typical
-------------------------	--------------

NOTE

*Also available 120/208 VAC, adjustable $\pm 10\%$

**Use 28VDC output only during engine start mode

FIGURE 1

