



MOBILE CONFIGURATION  
(Shown in Ramp Only Configuration)

## FoxAir Series Mobile HVAC 50Hz or 60Hz 21,000 BTU or 24,000 BTU

The FoxCart's FoxAir Series is a portable HVAC unit capable of delivering 21,000\* / 24,000\*\* BTU of refrigerated air for pre-cooling or maintenance operations, cooling 1,200 - 1,400 square feet, dependent upon ambient conditions. With an additional 11,000\* / 12,000\*\* BTU 'Heater' option, the FoxAir can create that comfortable climate year round.

### STANDARD FEATURES:

- Integral 20A Breaker / Switch
- Only 20A Service Required
- Sealed Refrigerant System for Unmatched Reliability and Performance
- 547\* / 590\*\* CFM Air Movement System
- Infrared Remote Control with Display
- Washable Anti-Microbial Air Filter
- Quick-Connect Collar for Quick and Easy Connection of Air Delivery Hose
- Maintenance Free Tires and Locking Swivel Casters

### INPUT:

Voltage Range	220 - 240 VRMS, 1Ø, 2 Wire, Plus Safety Ground
Frequency	50* / 60** Hz ± 10%
Compressor Rated Load	9.5* / 10.5** Amps
Safety Disconnect	Circuit Breaker ON / OFF

### ENVIRONMENTAL:

Refrigerant Type / Qty	R410A - 47.3* / 41** oz
Moisture Protection	IP24
Air Filter	Washable
Sound Level	62* / 67** dBA

### INDICATORS:

Min Ambient Temp	Cooling for ≈ 1,200 - 1,400 Sq. Ft. Area - 64°F
Max Ambient Temp	Heating - 110°F (Requires Heat Option)

(Special Notes)

\*Applies Specifically to 50Hz Unit

\*\*Applies Specifically to 60Hz Unit

### OPTIONS:

- 11,000\* / 12,000\*\* BTU Heater
- Air Delivery Hose (Steel Reinforced 10" Diameter)
- Drain Hose Kit - 50' or 100' Feet (Specify)
- 50' or 100' Foot Input Power Cable (Pigtail - Specify)

### MECHANICAL SPECIFICATIONS:

Size:	See Figure 1
Weight:	261lbs (119kg)

(Weight Varies with Options)

### OPERATING CONDITIONS:

Adjustable Fan Speeds	Auto, Low, Medium, High* Low, High**
Modes	Auto, Cool, Dry, Fan Only* Economy, Cool, Fan Only**

### CONTROLS:

Timer	24 Hour
Temperature	via Remote

### CAPACITY RATINGS (OUTPUT):

Cooling BTU / Tons	21,000 / 1.75* 24,000 / 2.00**
Heating (Optional)	11,000* / 12,000** BTU
Airflow	547* / 590** CFM
Moisture Removal	5.2* / 6.8** Pints per Hour
Energy Efficiency Ratings	
SEER	4.8* / 10.4**
EER	3.0* / 2.75**

# GENERAL SPECIFICATIONS:

Specifications subject to change without notice

Rev B

